

Remote Surveillance and Security system





- Stability: Embedded feature. Avoids system crash, virus attack and program upgradeable through internet.
- Video / Audio: Up to 32 videos /16 audios recording, remote/local audio listening.
- Recording Modes: Continuous, Alarm, Motion Detection, Instant & Scheduled.
- **E-Z Playback Search:** Search by Time, Date, Event & Cameras and playback up to 16 cameras simultaneously.
- LAN Playback: EzLANPlayback software allows playback of video clips via
- Intelligent Search: Narrowing search of specific regions from the recorded video and the video that is retrieved will show exactly when the object appeared or disappeared.
- Motion Detection: Built-In Software can be set up with selectable zones & sensitivity control.
- Pre-Alarm Function: Complete coverage of an event, seconds of video prior to motion detected by the camera will be recorded, when enabled.
- Watermark: Built-In Digital Watermark.
- e-Map: Indicating the locations of the cameras, sensors and Fingerprint controller.
- Alarm Notification: Via phone, email or live video, when triggered
- **Event log records:** Show records for logins/logouts, video loss, remote access, HDD failure, motion detection, POS text and Access controller text.
- Triplex Operation: Simultaneous Recording, Playback and Remote-Viewing.
 - Dynamic IP Solution: With no static IP, with our optional "ID Codes" we connect them for you.
- **Mobile Phone Remote Viewing:** Supports mobile phone for remote monitoring.
- Web Browser/I.E.: Connect to multiple sites simultaneously and record /download /playback video clips at any remote location via Web Browser/I.E., View/playback up to 36 cameras per screen viewing from anywhere at any time.
- Remote Online Support: Users can remote access the DVR to change local settings/configurations if and when necessary, without the need for a site visit.
- Surge Protection: Each video input builds in a 25KV surge protector to avoid the damage of DVR from video-in voltage surges of nearby electrostatic strikes.
- Integrated Fingerprint Access Controller



ltem / Model	DSecu-3404HS	DSecu-1908ASE	DSecu-1916ASE	DSecu-1932ASE
Operating System	Embedded O.S.			
Video Input	4	8	16	32
Audio Recording	4	8	16	
Compression	MPEG 4			
Recording Rate	NTSC:120FPS PAL: 100FPS	NTSC:240FPS ; PAL: 200FPS		
Resolution	352x240/352x 288, 704x288/704x240, 704x480/704x576			
Frame Size*2	1 K~3K/Frame @ 352x240 ; 4.5K ~7K/Frame @ 704*480			
Network	10/100/1000 Mbps Ethernet			
HDD Capacity	2 HDD (Install by user); Up to 2 TB			
DVD±RW	Yes			
Back Up	CD-RW, DVD±RW, USB2.0 or LAN			
VGA Port	VGA monitor display			
Video Out	Yes			
Auto Recovery	Yes			
Watchdog Timer	Yes			
Time Stamp	Yes			
Panic Button	Yes			
Remote Controller	Yes			
Alarm In/Out	16 Alarm input / 6 Relay output (Option)			
P/T/Z Control	Yes (Option)			
POS Text Insert	Insert POS transaction data (Option)			
Access Controller	Integrate Fingerprint Access controller (Option)			
Weight & Size	Approx. 12 Kg / 380 x135 x355 (mm)			
Temperature	Operation: 0-50°C (Non- Condensing) Storage: -10-60°C (Non- Condensing)			

Order Information:

DScu-3404HS: 4 video input; 120/100 FPS recording Digital Video Recorder. DScu-3404HS-A: 4 video/4 audio input; 120/100 FPS recording Digital Video Recorder. DScu-1908ASE: 8 video input; 240/200 FPS recording Digital Video Recorder.

DScu-1908ASE -A: 8 video/8 audio input; 240/200 FPS recording Digital Video Recorder. DScu-1916ASE: 16 video input; 240/200 FPS recording Digital Video Recorder.

DScu-1916ASE -A: 16 video/16 audio input; 240/200 FPS recording Digital Video Recorder.

DScu-1932ASE: 32 video input; 240/200 FPS recording Digital Video Recorder. DScu-1932ASE -A: 32 video /16 audio input; 240/200 FPS recording Digital Video Recorder.



2F, No 70, Min De Rd, Chutung, Hsinchu, Taiwan, R.O.C. Http://www.i-view.com.tw

Tel: 886-3-5103001

Note:

DSecu is trademark[©] 2005 of I-View Communication Inc.

4. All other trademarks belong to their respective own

Fax: 886-3-5103002





