## **INSTALLATION STEPS:**

## **OPERATION INSTRUCTION**

Click the + button to increase a new site. Then, insert and adjust the information of connecting device which is including "name", "ip", "port", "account", "password", "resolution" and "channel". Finally, click setting.





2. Click the setup site to perform connecting.



2.1

I

Site: Within this tag, it will present all of the setup sites. To click + button can increase the new site. Moreover, while press the setup site for a few seconds, the user can "edit" the information or "delete" the site. The presented image will show as following,



2.2 Photo: Among this tab, the snapshot images can be seen in this tab.

2.3 Setting: Within this tag, the user can setup the storage path of snapshot image and the application language. Currently, there are English, traditional Chinese, simplified Chinese and Portuguese four options. The presented image as the following,



3. Within the live view, all of the control and setting buttons are put in the bottom of this page.



ICON	ACTION	INSTRUCTION	NOTE	
	Site test01 1wad Cancel	Switch the setup sites.		
	Resolution   QCIF   CIF   VGA   D1   Cancel	Switch the image resolution of connecting device (DVR or IPCAM).		
Ð	Channel   1 Image: Channel   2 Image: Cancel	Switch the channel of connecting DVR.		
н		Pause or Play the connection		
۲		Enable or disable the two-way audio function.	The IPCAM enable function.	Connecting has to two-way

		While connecting the ptz device,	PTZ	IPCAM	
		the PTZ control panel will pop-up	connection		
		and the user can click these			
		buttons to control pan/ tilt/ Zoom.			
$\Xi$	FULL	SCREEN/	Click this button can switch the		
	QRIGINAL SIZE		displayed size of connecting		
			device between full screen size		
			and original size.		
Ô	SNAPSHOT		Click this button to reserve the	User has t	o setup
			wanted image.	the storage path of	
				snapshot im	age.